



INEO INSTALLATION SYSTEM

Installation element slim with cistern for wallhung WC and for shower toilet

INEOLINK H920110

TECHNICAL DATA

Order no.	H920110
Certified to	EN 14055, EN 1519
matching for	Shower toilet ready
Specifications	Self-supporting steel frame for covering with plasterboard, installation onto a solid wall, in drywall constructions. Construction height 1155 mm. Conduit pipe for feed pipe of shower toilet pre-assembled With support for WC ceramic with small contact surfaces. With front operated. Cistern pre-assembled, Dual-Flush 6/3-l (4.5/3-l, 4/2.6-l-flush), with water condensation insulation. Non-slip leg supports, rotatable foot plates, height-adjustable 0-200 mm. Capable to resist 400 kg
Water inlet	top R 1/2, brass, matching for standard pipe systems

Outlet	DN 90/110, pipe clamp with depth adjustable
Flow pressure range	0.5-10 bar
Water temperature	max. 25°C
Tank	Installation depth: 90 mm, material PP
Installation depth	93-140 mm
Weight	15,0 kg
Mounting acc. incl.	Angle valve 1/2", protection box for service opening, protection set with cover, fastening material and 2x M12 threaded rods, WC connection set DN 90, HDPE, Drain elbow DN 90, HDPE with adapter DN 90/110, HDPE.
Mounting acc. excl.	Sound insulation set, order no. VS16032 C00 000 0
Accessories excl.	Flush plates INEO, dual flush with front actuation
Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation.
Otherwise	Compatible with U-profiles UW 50, UW 75.
Colours	Surface powder coated

TECHNICAL DRAWINGS / S 1 : 20

