SET PRO / PRO X

Cistern
82995.1



TECHNICAL DATA

Order no.	82995.1
Certified to	EN 14055
matching for ,	Floorstanding WC pan silent flush Pro X order no. 82486.1 / Charge 000 Floorstanding WC pan Laufen Pro, order no. 82595.1, 82595.2, 82595.8 / Charge 000, 82596.2 / Charge 000, 82596.4
Specification	Flushing mechanism Dual-Flush With water condensation insulation: Charge 971 – 5/3-l (6/3-l-flush, 4,5/3-l-flush) Without water condensation insulation: Charge 974 – 5/3-l (6/3-l-flush, 4,5/3-l-flush)
Water inlet	rear, 1/2” brass
Weight	13,0 kg
Mounting acc. incl.	Fastening kit Angle valve for rear water inlet Water inlet hose
Colours	see colour table

SPECIFICATION TEXT

Cistern Laufen-PRO / PRO X, sanitary ceramic
EN 14055, dimensions 375 x 160 x 395 mm
Dual-Flush 5/3-l (6/3-l-flush, 4,5/3-l-flush)
water inlet rear, 1/2” brass
matching floorstanding WC pan silent flush Pro X, order no. 82486.1/ option 000 and floorstanding WC pan Laufen Pro order no. 82595.1/ option 000, 82595.2, 82595.8/option 000, 82596.2/option 000, 82596.4
Special feature: with or without water condensation insulation
Order no. 82995.1

TECHNICAL DRAWINGS / S 1 : 20

