

**Shower toilet, rimless, wall-hung
with remote control,
with hotel software
with seat and cover
82069.1 ... HTV 1**


TECHNICAL DATA

Order no.	82069.1 ... HTV 1	WC seat and cover	Duroplast, removable, with lowering system
Certified to	CE, IPX4, EN 13077, SVGW Drinking water standards EN 1717	Power supply & consumption	concealed Rated voltage 220 to 240 V, 50/60 Hz Direct connection by NYM cable possible
matching for	LIS CW2 Concealed frame with cistern for shower toilets, order no. 89466.1	Power supply & consumption	Power consumption in use max. 1'400 W Power consumption in standby (boiler at ECO or OFF, LED display OFF) < 1 W Protection rating IPX4 Protection class I
Specifications	Shower toilet, rimless, wall-hung, with ceramic surface refinement LCC (only white) Washdown, flushing from 6 l to 4.5 l, concealed fixation Controller with rotary button for shower function	Weight	40,0 kg
Functions	Rear shower and lady shower adjustable in pressure, position and temperature, shower duration range 15-20-25 sec Oscillating and pulsating cleaning mode Self cleaning of shower head before and after every use Automatic air purifier with active carbon filter Descaling programme Thermal cleaning heats up the entire water-carrying system with water heated to 70°C Light with signaling feature	Accessories incl.	Touch screen remote control, with AAA batteries and wall holder Carbon filter, splash protection User manual
Hotel software	Operating functions visible to the guest on the remote control, adjustment / maintenance functions hidden. Activation of hidden functions and system advice for decalcification or thermal cleaning via remote control. Optional: own logo in the remote control programmable on the main screen.	Mounting acc. incl.	Inlet and outlet pipes, fastening kit M12 with mounting plate, sound insulation set (DIN 4109) and water connection set for shower toilet Mounting instruction
Water pressure & temperature	Shower 7 pressure levels Flow rate ca. 4.3 l/min, Power mode ca. 5.6 l/min, Lady shower ca. 2.5 l/min Shower 7 temperature level	Mounting acc. excl.	Adapter plate for Cleanet Riva Shower Toilet, order no. 89469.0 Stone screw fastening kit M12
Water inlet	concealed, G 3/8"	Colours	400 – White LCC, 757 – White matt
Outlet	DN 110 mm horizontal	SPECIFICATION TEXT Shower toilet, rimless, wall-hung, washdown Laufen CLEANET RIVA toilet pan sanitary ceramic, with ceramic surface refinement LCC (only white) WC seat and cover Duroplast, removable, with lowering system CE, IPX4, EN 13077, SVGW, Drinking water standards EN 1717 min. 4.5/3-l-flush, dimensions 395 x 605 x 405 mm, concealed fixation Special feature: Touch screen remote control with hotel software, rear shower and lady shower, with adjustable water pressure, temperature and nozzle position, oscillating and pulsating cleaning mode, integrated self cleaning shower head before and after every use, integrated odour filter, light with signaling feature, water supply and power supply concealed Order no. 82069.1 ... HTV 1	

TECHNICAL DRAWINGS / S 1 : 20
