

Floorstanding cistern, two-part Universal for floorstanding WC pan
82966.1



TECHNICAL DATA

Order no.	82966.1
Certified to	EN 14055
matching for	Floorstanding WC pan, order no. 82295.2 Floorstanding WC pan rimless, order no. 82295.6
Specification	Floorstanding, consisting of two-parts Flushing mechanism Dual-Flush water condensation insulation Charge 981 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)
Water inlet	concealed top left rear, 1/2" brass
Weight	21,0 kg
Mounting acc. incl.	Fastening kit Angle valve for rear water inlet Water inlet hose

Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 220 - 290 mm only LAUFEN-connection, order no. 89902.5
---------------------	--

Colours see colour table

SPECIFICATION TEXT

Floorstanding cistern, two-part Universal LAUFEN PRO,
sanitary ceramic
EN 14055
dimensions 400/410 x 140 x 980 mm
Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush)
concealed water inlet top left rear, 1/2" brass
matching floorstanding WC pan, order no. 82295.2 and floorstanding
WC pan rimless, order no. 82295.6
Special feature: water condensation insulation
Order no. 82966.1

TECHNICAL DRAWINGS / S 1 : 20

