

CLEANET SIT LITE

Shower toilet seat and cover, with lateral connections, 89G89.0



TECHNICAL DATA

Order no.	89G89.0
Certified to	CCE, IPX4, EN1717
Specifications	Duroplast, with antibacterial treatment, with lowering system with quick release function for cleaning iOS and android app. connection
Water inlet	G 3/8" (male)
Working pressure	0.1 to 0.7 Mpa (1-7 bar)
Working temperature	+5 to +35 °C
Cleaning functions	Rear shower and lady shower 5 levels pressure adjustment 5 levels nozzle position adjustment 5 levels temperature adjustment Oscillating and pulsating cleaning mode
Dryer function	5 levels temperature adjustment
Comfort	Night light (bowl and ambience) Remote operation possible
Hygiene	Automatic self cleaning of nozzle and descaling process UV nozzle disinfection

Power supply & consumption	220-240V, 50/60Hz, plug type F Power saving mode Power cord length 1m
Weight	7,8 kg
Mounting acc. incl.	Fastening kit Mounting instruction
Mounting acc. incl.	Remote control, order no. 89G89.6
Colours	000 – White

SPECIFICATION TEXT

Shower toilet seat and cover CLEANET SIT LITE
Duroplast, with antibacterial treatment, with quick release function for cleaning
CCE, IPX4, EN1717, AC 220-240V, 50/60Hz, plug type F
dimensions 370 x 490 x 85 mm
Special feature: rear shower and lady shower, with adjustable water pressure, temperature and nozzle position, oscillating and pulsating cleaning mode, automatic self cleaning nozzle and descaling process, UV nozzle disinfection, soft closing lid and seat, integrated night light, power saving mode, iOS and android app. connection
Order no. 89G89.0

TECHNICAL DRAWINGS / S 1 : 20

