

# Luminex bathtub with integrated LED Panel and remote control freestanding version 23028.2 T00 617 1



## TECHNICAL DATA

|                                   |                                                                                                                                                                                                                                                                                                   |                          |                                                                                                                         |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Order no.                         | 23028.2 T00 617 1                                                                                                                                                                                                                                                                                 | Power supply             | concealed                                                                                                               |
| Certified to                      | EN 14516 (EN 198), EN 232                                                                                                                                                                                                                                                                         |                          | Rated voltage 220 to 240 V, 50/60 Hz                                                                                    |
| Dimensions                        | 1600 x 750 mm                                                                                                                                                                                                                                                                                     |                          | Protection rating power supply IP67                                                                                     |
| Hight                             | 560 mm                                                                                                                                                                                                                                                                                            | Weight                   | 106,0 kg                                                                                                                |
| Depth                             | 450 mm                                                                                                                                                                                                                                                                                            | Mounting acc. incl.      | Remote control, with 3 AAA batteries and wall holder, black, order no. 29228.2                                          |
| Use capacity                      | 275 litre (total: 345 litre)                                                                                                                                                                                                                                                                      |                          | LED panel, order no. 29228.1                                                                                            |
| Specification                     | Freestanding bathtub made of Luminex with integrated LED Panel without overflow slot incl. click-clack waste with integrated overflow function and white matt cover with integrated LED panel under the tub floor LED panel replaceable Charge 617 – bathtub with LED panel, without whirl system |                          | Power supply unit (mounted outside the bathtub)                                                                         |
|                                   |                                                                                                                                                                                                                                                                                                   |                          | Connection cable for LED panel, length 10 m with 2x2.5 mm <sup>2</sup>                                                  |
|                                   |                                                                                                                                                                                                                                                                                                   |                          | Click-clack waste with integrated overflow function and siphon cover with valve plate in white matt, order no. 29228.3  |
|                                   |                                                                                                                                                                                                                                                                                                   |                          | Flex-pipe 1m, order no. 29443.9                                                                                         |
| Functions for lighting management | Lighting scenarios can be set via remote control (on-off/scenario selection/dimming) 9 lighting programs, each with 3 lighting scenarios, can be selected via the remote control                                                                                                                  | Installation requirement | Cut-out in the floor is needed for housing the siphon. An empty pipe for the connecting cable must be provided on site. |
|                                   |                                                                                                                                                                                                                                                                                                   | Colours                  | T00 – White Translucent                                                                                                 |

## TECHNICAL DRAWINGS / S 1 : 40

