

# CLEANET PRO LITE

## Shower toilet, with hidden connections WC combination rimless, floorstanding 615890 000 S00 2



### TECHNICAL DATA

Order no.	615890 000 S00 2	Power supply & consumption	Rated voltage 220-240V, 50/60Hz Power consumption in use max. 1650W Power saving mode Power cord length 1m
Certified to	SIT: CE, IPX4, EN1717 WC: EN 997 / EN 33	Weight	34,8 kg
Specifications	SIT: Duroplast, with hidden connections, with antibacterial treatment, with lowering system Lid with quick release function for cleaning Electric Bidet easy to lift for cleaning iOS and android app. connection WC: Floorstanding WC combination rimless, washdown for 4,5/3-l-flush, Laufen Pro, order no. 825962 000 S00 1, 2 fixing holes, without lateral holes	Accessories incl.	SIT: Flexible hose Splash protection User manual
WC outlet	horizontal VARIO, vertical 70 - 260 mm	Accessories excl.	WC: Cistern Laufen Pro, with water inlet rear, order no. 82995.1 side left and side right, order no. 82995.2
Water inlet	G 3/8" (male)	Mounting acc. incl.	SIT: Mounting instruction Installation template, order no. WK2ES42004002 Mounting set incl. fastening kit, order no. 89389.3 WC: Fixing set, order no. 89175.7
Working pressure	0.1 to 0.7 Mpa (1-7 bar)	Mounting acc. excl.	SIT: Fastening kit Direct electrical connector, order no. 89F892 Electro cable with EU-plug (type F), order no. 89E890 Electro cable with CH-plug (type J), order no. 89E891 Remote control, order no. 89G896 WC: for VARIO-outlet 70 - 160 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 160 - 260 mm only LAUFEN-connection, order no. 89902.5 Flexible hose pack, order no. A805037500
Working temperature	+5 to +35 °C	Colours	000 – White
Cleaning functions	Rear shower and lady shower 5 levels pressure adjustment 5 levels nozzle position adjustment 5 levels temperature adjustment Oscillating and pulsating cleaning mode		
Comfort	Night light (bowl and ambience) Remote operation possible 5 user profiles Integrated descaling function		
Hygiene	Self cleaning of shower head before and after every use Exchangeable shower nozzle tip UV nozzle disinfection		

# CLEANET PRO LITE

Shower toilet,  
with hidden connections  
WC combination rimless,  
floorstanding  
615890 000 S00 2



## TECHNICAL DRAWINGS / S 1 : 20

