

INEO

INEOLINK concealed cistern for wall-hung WC and shower WC

DIMENSIONS

Length	500 mm
Width	135 mm
Height	1120 mm



#mountingAccessoriesExcluded_text

LAUFEN INEO Flush Plate with two-cable activation
 LAUFEN INEO Flush Plate with sensor-motor activation

Optional:

Sound absorber pads VS16032C000000

Spare parts and many more accessories available

Average water consumption (L.) : 3.38

Bullet Point I : Pre-assembled LAUFEN INEOLINK installation element for wall-hung WC and shower WC. It is improved for a most easy and rapid single-person installation in dry-wall and pre-wall situations

Bullet Point II : With a height adjustability system with friction-braked legs (0...200 mm) and with tool free depth-adjustment (135...205 mm)

Bullet Point III : Feet can be rotated to fit common UW50 and UW75 profiles, as well as the LAUFEN INEOGRID system. It has tool-free fastening and cable connections for flush plates

Bullet Point IV : The dual flush is preset to 6l/4.5l and can be adjusted down to 4l/2l. Flushing performance can be adjusted on the fly, without disassembly of the flush valve, to avoid over-splashing. All internal components can be replaced and maintained without the use of tools either

Bullet Point V : INEOLINK are designed for perfect compatibility with the wide range of LAUFEN INEO Flush Plates and LAUFEN ceramic products including toilets, urinals, washbasins, and bidets

Elbow connection : DN90 (90 mm)

Flushing volume preset : Dual flush 3/6 litres

Net weight (kg) : 13.65

Operating panel position : Frontal

Suitable for : Wall-hung WC