

INEO

INEOLINK slim (80 mm) brickwall concealed cistern for floorstanding WC



#mountingAccessoriesExcluded_text

LAUFEN INEO Flush Plate with two-cable activation
 LAUFEN INEO Flush Plate with sensor-motor activation
 Spare parts and many more accessories available

Bullet Point I : Pre-assembled LAUFEN INEOLINK concealed cistern for floorstanding WC.

Bullet Point II : It has tool-free fastening and cable connections for flush plates. The plate position can be either from front or from the top. The dual flush is preset to 6l/3l and can be adjusted down to 4l/2l. Flushing performance can be adjusted on the fly, without disassembly of the flush valve, to avoid over-splashing. All internal components can be replaced and maintained without the use of tools either

Bullet Point III : INEOLINK are designed for perfect compatibility with the wide range of LAUFEN INEO Flush Plates and LAUFEN ceramic products including toilets, urinals, washbasins and bidets

Bullet Point IV : H92610450000001 complies with EN 14055

Commodity Code/Import Code Number for Foreign Trad : 39229000

Dynamic pressure range : 0,5 - 10 Bar

Flushing volume preset : Dual flush 3/6 litres

Material : Plastic

Maximum Temperature (°C) : 25

Net weight (kg) : 3.5

Operating panel position : Frontal

Suitable for : Floor-standing toilet

Tank depth (mm) : 80

Water inlet position : Top